



Half Controlled Single Phase Rectifier Bridge

Including Freewheeling Diode and Field Diodes

$$V_{RRM} = 800-1600 \text{ V}$$

$$I_{dAVM} = 21 \text{ A}$$

V_{RSM} V_{DSM} V	V_{RRM} V_{DRM} V	Type
900	800	VHFD 16-08io1
1300	1200	VHFD 16-12io1
1700	1600	VHFD 16-16io1



Bridge and Freewheeling Diode

Symbol	Conditions	Maximum Ratings	
I_{dAV}	$T_H = 85^\circ\text{C}$, module	16	A
I_{dAVM}^*	module	21	A
I_{FRMS}, I_{TRMS}	per leg	15	A
I_{FSM}, I_{TSM}	$T_{VJ} = 45^\circ\text{C};$ $V_R = 0 \text{ V}$	$t = 10 \text{ ms}$ (50 Hz), sine	150 A
		$t = 8.3 \text{ ms}$ (60 Hz), sine	170 A
	$T_{VJ} = T_{VJM}$ $V_R = 0 \text{ V}$	$t = 10 \text{ ms}$ (50 Hz), sine	130 A
		$t = 8.3 \text{ ms}$ (60 Hz), sine	140 A
I^2t	$T_{VJ} = 45^\circ\text{C}$ $V_R = 0 \text{ V}$	$t = 10 \text{ ms}$ (50 Hz), sine	110 A ² s
		$t = 8.3 \text{ ms}$ (60 Hz), sine	120 A ² s
	$T_{VJ} = T_{VJM}$ $V_R = 0 \text{ V}$	$t = 10 \text{ ms}$ (50 Hz), sine	85 A ² s
		$t = 8.3 \text{ ms}$ (60 Hz), sine	80 A ² s
$(di/dt)_{cr}$	$T_{VJ} = 125^\circ\text{C}$ $f = 50 \text{ Hz}, t_p = 200 \mu\text{s}$ $V_D = 2/3 V_{DRM}$ $I_G = 0.3 \text{ A},$ $di_G/dt = 0.3 \text{ A}/\mu\text{s}$	repetitive, $I_T = 50 \text{ A}$	150 A/ μs
		non repetitive, $I_T = 0.5 I_{dAV}$	500 A/ μs
$(dv/dt)_{cr}$	$T_{VJ} = T_{VJM}; V_{DR} = 2/3 V_{DRM}$ $R_{GK} = \infty$; method 1 (linear voltage rise)	1000	V/ μs
V_{RGM}		10	V
P_{GM}	$T_{VJ} = T_{VJM}$ $I_T = 0.5 I_{dAVM}$	$t_p = 30 \mu\text{s}$	$\leq 10 \text{ W}$
		$t_p = 500 \mu\text{s}$	$\leq 5 \text{ W}$
		$t_p = 10 \text{ ms}$	$\leq 1 \text{ W}$
P_{GAVM}			0.5 W
T_{VJ}		-40...+125	$^\circ\text{C}$
T_{VJM}		125	$^\circ\text{C}$
T_{stg}		-40...+125	$^\circ\text{C}$
V_{ISOL}	50/60 Hz, RMS	$t = 1 \text{ min}$	3000 V~
	$I_{ISOL} \leq 1 \text{ mA}$	$t = 1 \text{ s}$	3600 V~
d_s	Creep distance on surface	12.7	mm
d_A	Strike distance in air	9.4	mm
a	Max. allowable acceleration	50	m/s ²
M_d	Mounting torque (M5)	2-2.5	Nm
	(10-32 UNF)	18-22	lb.in.
Weight		35	g

Features

- Package with DCB ceramic base plate
- Isolation voltage 3600 V~
- Planar passivated chips
- Blocking voltage up to 1600 V
- Low forward voltage drop
- Leads suitable for PC board soldering
- UL registered E 72873


Applications

- Supply for DC power equipment
- DC motor control

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling

Dimensions in mm (1 mm = 0.0394")



Symbol	Conditions		Characteristic Values		
I_R, I_D	V_R = V_{RRM}; V_D = V_{DRM}	T_{VJ} = T_{VJM}	≤	5	mA
		T_{VJ} = 25°C	≤	0.3	mA
V_T, V_F	I_T, I_F = 45 A; T_{VJ} = 25°C		≤	2.55	V
V_{T0}	For power-loss calculations only (T _{VJ} = 125°C)			1.0	V
r_T				40	mΩ
V_{GT}	V_D = 6 V;	T_{VJ} = 25°C	≤	1.0	V
		T_{VJ} = -40°C	≤	1.2	V
I_{GT}	V_D = 6 V;	T_{VJ} = 25°C	≤	65	mA
		T_{VJ} = -40°C	≤	80	mA
		T_{VJ} = 125°C	≤	50	mA
V_{GD}	T_{VJ} = T_{VJM};	V_D = 2/3 V_{DRM}	≤	0.2	V
I_{GD}	T_{VJ} = T_{VJM};	V_D = 2/3 V_{DRM}	≤	5	mA
I_L	I_G = 0.3 A; t_G = 30 μs; di_G/dt = 0.3 A/μs;	T_{VJ} = 25°C	≤	150	mA
		T_{VJ} = -40°C	≤	200	mA
		T_{VJ} = 125°C	≤	100	mA
I_H	T_{VJ} = 25°C; V_D = 6 V; R_{GK} = ∞		≤	100	mA
t_{gd}	T_{VJ} = 25°C; V_D = 0.5V_{DRM} I_G = 0.3 A; di_G/dt = 0.3 A/μs		≤	2	μs
t_q	T_{VJ} = 125°C, I_T = 15 A, t_p = 300 μs, V_R = 100 V		typ.	150	μs
Q_r	di/dt = -10 A/μs, dv/dt = 20 V/μs, V_D = 2/3 V_{DRM}			75	μC
R_{thJC}	per thyristor (diode); DC current			2.4	K/W
	per module			0.6	K/W
R_{thJH}	per thyristor (diode); DC current			3.0	K/W
	per module			0.75	K/W

Field Diodes

Symbol	Conditions	Maximum Ratings
I_{FAV}	$T_H = 85^\circ\text{C}$, per Diode	4 A
I_{FAVM}	per diode	4 A
I_{FRMS}	per diode	6 A
I_{FSM}	$T_{VJ} = 45^\circ\text{C};$ $V_R = 0$ V $t = 10$ ms (50 Hz), sine $t = 8.3$ ms (60 Hz), sine	100 A 110 A
	$T_{VJ} = T_{VJM}$ $V_R = 0$ V $t = 10$ ms (50 Hz), sine $t = 8.3$ ms (60 Hz), sine	85 A 94 A
I^2t	$T_{VJ} = 45^\circ\text{C}$ $V_R = 0$ V $t = 10$ ms (50 Hz), sine $t = 8.3$ ms (60 Hz), sine	50 A ² s 50 A ² s
	$T_{VJ} = T_{VJM}$ $V_R = 0$ V $t = 10$ ms (50 Hz), sine $t = 8.3$ ms (60 Hz), sine	36 A ² s 37 A ² s
I_R	$V_R = V_{RRM}$ $T_{VJ} = T_{VJM}$ $T_{VJ} = 25^\circ\text{C}$	1 mA 0.15 mA
V_F	$I_F = 21$ A; $T_{VJ} = 25^\circ\text{C}$	1.83 V
V_{T0}	For power-loss calculations only ($T_{VJ} = 125^\circ\text{C}$)	0.9 V
r_T		50 mΩ
R_{thJC}	per diode; DC current	4.4 K/W
R_{thJH}	per diode; DC current	5.2 K/W

Data according to IEC 60747 and refer to a single thyristor/diode unless otherwise stated.

* for resistive load




Fig. 1 Gate trigger range




Fig. 2 Gate controlled delay time t_{gd}




Fig. 3 Forward current vs. voltage drop per diode




Fig. 4 Surge overload current




Fig. 5 I^2t versus time per diode




Fig. 6 Power dissipation vs. direct output current and ambient temperature




Fig. 7 Max. forward current vs. heatsink temperature




Fig. 8 Transient thermal impedance junction to heatsink

Constants for Z_{thJH} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.01	0.008
2	0.4	0.05
3	1.69	0.06
4	0.9	0.25