

■Taping Specification for Automatic Insertion(Mounting)

Refer to the PDF file of taping specifications

■Rating, Dimensions & Quantity/Reel

Cap. (μF)	Rated volt. 16VDC						Rated volt. 50VDC						Rated volt. 100VDC												
	Part No.	Dimensions (mm)			Code	Q'ty	Part No.	Dimensions (mm)			Code	Q'ty	Part No.	Dimensions (mm)			Code	Q'ty							
		L	W	H				L	W	H				L	W	H									
0.001	For this rating use type ECHU(B)						For this rating use type ECHU(B)						ECWU1102JB5	3.2	1.6	1.0	H2	3000							
0.0012													ECWU1122JB5	3.2	1.6	1.0	H2								
0.0015													ECWU1152JB5	3.2	1.6	1.0	H2								
0.0018													ECWU1182JB5	3.2	1.6	1.0	H2								
0.0022													ECWU1222JB5	3.2	1.6	1.0	H2								
0.0027													ECWU1272JB5	3.2	1.6	1.0	H2								
0.0033							For this rating use type ECHU(B)						ECWU1H332JB5	3.2	1.6	0.8	H1	3000	ECWU1332JB5	3.2	1.6	1.4	H3	2000	
0.0039													ECWU1H392JB5	3.2	1.6	0.8	H1		ECWU1392JB5	3.2	1.6	1.4	H3		
0.0047													ECWU1H472JB5	3.2	1.6	0.8	H1		ECWU1472JB5	3.2	1.6	1.4	H3		
0.0056													ECWU1H562JB5	3.2	1.6	0.8	H1		ECWU1562JB5	3.2	2.5	1.4	G2		
0.0068													ECWU1H682JB5	3.2	1.6	0.8	H1		ECWU1682JB5	3.2	2.5	1.4	G2		
0.0082													ECWU1H822JB5	3.2	1.6	1.0	H2		ECWU1822JB5	3.2	2.5	2.0	G3		
0.01													ECWU1H103JB5	3.2	1.6	1.0	H2	ECWU1103JB5	3.2	2.5	2.0	G3			
0.012	ECWU1C123JB5	3.2	1.6	1.0	H2	3000							ECWU1H123JB5	3.2	2.5	1.0	G1	2000	ECWU1123JC9	4.8	3.3	1.4	E1		3000
0.015	ECWU1C153JB5	3.2	1.6	1.0	H2								ECWU1H153JB5	3.2	2.5	1.0	G1		ECWU1153JC9	4.8	3.3	1.4	E1		
0.018	ECWU1C183JB5	3.2	1.6	1.0	H2								ECWU1H183JB5	3.2	2.5	1.4	G2		ECWU1183JC9	4.8	3.3	1.4	E1		
0.022	ECWU1C223JB5	3.2	1.6	1.0	H2		ECWU1H223JB5	3.2	2.5	1.4	G2	ECWU1223JC9	4.8	3.3	1.4	E1									
0.027	ECWU1C273JB5	3.2	1.6	1.0	H2	2000	ECWU1H273JB5	3.2	2.5	1.4	G2	ECWU1273JC9	4.8	3.3	1.4	E1									
0.033	ECWU1C333JB5	3.2	1.6	1.4	H3		3000	ECWU1H333JB5	3.2	2.5	2.0	G3	ECWU1333JC9	4.8	3.3	1.4	E1								
0.039	ECWU1C393JB5	3.2	1.6	1.4	H3			ECWU1H393JB5	3.2	2.5	2.0	G3	ECWU1393JC9	4.8	3.3	2.0	E2								
0.047	ECWU1C473JB5	3.2	1.6	1.4	H3			ECWU1H473JB5	3.2	2.5	2.0	G3	ECWU1473JC9	4.8	3.3	2.0	E2								
0.056	ECWU1C563JB5	3.2	2.5	1.4	G2	2000		ECWU1H563JC9	4.8	3.3	2.0	E2	3000												
0.068	ECWU1C683JB5	3.2	2.5	1.4	G2		ECWU1H683JC9	4.8	3.3	2.0	E2	2000													
0.082	ECWU1C823JB5	3.2	2.5	2.0	G3		ECWU1H823JC9	4.8	3.3	2.4	E3a														
0.1	ECWU1C104JB5	3.2	2.5	2.0	G3		ECWU1H104JC9	4.8	3.3	2.4	E3a														
0.12	ECWU1C124JC9	4.8	3.3	1.4	E1	3000	ECWU1H124JC9	6.0	4.1	1.8	D1		2000												
0.15	ECWU1C154JC9	4.8	3.3	2.0	E2		ECWU1H154JC9	6.0	4.1	2.0	D2														
0.18	ECWU1C184JC9	4.8	3.3	2.0	E2		ECWU1H184JC9	6.0	4.1	2.4	D3														
0.22	ECWU1C224JC9	4.8	3.3	2.4	E3a		ECWU1H224JC9	6.0	4.1	2.8	D4														
0.27	ECWU1C274JC9	6.0	4.1	1.8	D1	3000					2000														
0.33	ECWU1C334JC9	6.0	4.1	2.0	D2																				
0.39	ECWU1C394JC9	6.0	4.1	2.4	D3																				
0.47	ECWU1C474JC9	6.0	4.1	2.8	D4																				

■Example for Land Dimensions (mm)

Cade	Land dimensions		
	Reflow soldering		
	A	B	C
H1	2.2	3.8	1.4
H2	2.2	3.8	1.4
H3	2.2	3.8	1.4
G1	2.2	3.8	2.3
G2	2.2	3.8	2.3
G3	2.2	3.8	2.3
E1	2.6	6.6	3.0
E2	2.6	6.6	3.0
E3a	2.6	6.6	3.0
E3	2.6	6.6	3.0
D1	3.8	7.8	3.8
D2	3.8	7.8	3.8
D3	3.8	7.8	3.8
D4	3.8	7.8	3.8