



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)**

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



# FSA8028

## Audio Jack Detection and Configuration Switch

### Features

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Detection             | Accessory Plug-In<br>3- or 4-Pole Audio Jack<br>Send/End Key Pressed |
| Functionality         | Decreased Timing for Sensitive<br>Send/End Keys                      |
| Switch Type           | MIC                                                                  |
| V <sub>DD</sub>       | 2.5 to 4.4 V                                                         |
| V <sub>IO</sub>       | 1.6 to V <sub>DD</sub>                                               |
| THD (MIC)             | 0.01% Typical                                                        |
| ESD (Air Gap)         | 15 kV                                                                |
| Operating Temperature | -40°C to 85°C                                                        |

### Description

The FSA8028 is an audio jack detector and switch for 3- or 4-pole accessories. In addition to detection, the FSA8028 features an integrated MIC switch that allows the processor to configure the audio jack. The architecture is designed to allow common third-party headphones to be used for listening to music from mobile handsets, personal media players, and portable peripheral devices.

- Determines 3- or 4-Pole Audio Jacks
- Removes Audio Jack Pop-n-Click Caused by MIC Bias
- Detects Audio Jack Accessories:
  - Standard Headphones
  - Headsets with MIC
  - Send / End Button Presses
- Integrates a MIC Switch for 4-Pole Configuration

### Applications

- 3.5 mm and 2.5 mm Audio Jacks
- Cellular Phones, Smart Phones
- MP3 and PMP

### Ordering Information

| Part Number | Operating Temperature Range | Top Mark | Package                                                                              |
|-------------|-----------------------------|----------|--------------------------------------------------------------------------------------|
| FSA8028UMX  | -40 to +85°C                | KZ       | 10-Lead, 1.4 x 1.8 x 0.55 mm, 0.4 mm Pitch, Ultrathin Molded Leadless Package (UMLP) |

## Pin Configuration



## Pin Descriptions

| Name  | Pin # | Type   | Description                                                                                                                                     | Function   |                           |
|-------|-------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------|
| DET   | 2     | Output | Indicates if an accessory is plugged into the audio jack, as detected on the J_DET pin                                                          | 0          | Plugged                   |
|       |       |        |                                                                                                                                                 | 1          | Unplugged                 |
| JPOLE | 4     | Output | Indicates if an accessory plugged into the audio jack is 3 pole or 4 pole                                                                       | 0          | 4-pole jack               |
|       |       |        |                                                                                                                                                 | 1          | 3-pole jack               |
| S/E   | 6     | Output | Indicates state of SEND/END for a 4-pole accessory when a key has been pressed                                                                  | 0          | No key press              |
|       |       |        |                                                                                                                                                 | 1          | Key press                 |
| EN    | 3     | Input  | Controls internal microphone switch between the J_MIC and MIC pins                                                                              | 0          | MIC / J_MIC switch open   |
|       |       |        |                                                                                                                                                 | 1          | MIC / J_MIC switch closed |
| J_DET | 10    | Input  | Input from a pin of the audio jack socket tied to a mechanical switch that typically closes whenever an audio jack is inserted into that socket | 0          | Plugged                   |
|       |       |        |                                                                                                                                                 | 1          | Unplugged                 |
| MIC   | 7     | Switch | Microphone switch path that goes to the microphone preamplifier                                                                                 | See EN pin |                           |
| J_MIC | 8     | Switch | Microphone switch path that connects to the microphone and SEND/END key audio jack pole                                                         |            |                           |
| VDD   | 5     | Power  | Core supply voltage                                                                                                                             |            |                           |
| VIO   | 1     | Power  | Baseband I/O supply voltage                                                                                                                     |            |                           |
| GND   | 9     | Ground | Ground for both the audio jack and the PCB                                                                                                      |            |                           |

### Note:

1. 0 =  $V_{OL}$  or  $V_{IL}$ ; 1 =  $V_{OH}$  or  $V_{IH}$



**Table 2. States During Power Good and OFF**

| State Description | VDD | VIO | DET              | EN      | JPOLE         | S/E             | J-DET               | MIC Switch |
|-------------------|-----|-----|------------------|---------|---------------|-----------------|---------------------|------------|
| Active            | 1   | 1   | Active           |         |               |                 |                     |            |
| OFF               | 0   | 0   | 1<br>(unplugged) | 3-State | 1<br>(3 Pole) | 0<br>(No Press) | HIGH<br>(unplugged) | Open       |
|                   | 1   | 0   |                  |         |               |                 |                     |            |
|                   | 0   | 1   |                  |         |               |                 |                     |            |

**Table 3. FSA8028 I/O States During Detection<sup>(3)</sup>**

| J_DET | J_MIC | EN | S/E          |              | JPOLE      |            | DET |
|-------|-------|----|--------------|--------------|------------|------------|-----|
|       |       |    | 3 Pole       | 4 Pole       | 3 Pole     | 4 Pole     |     |
| 0     | 1     | 1  | 0 (no press) | 0 (no press) | 0 (4 Pole) | 0 (4 Pole) | 0   |
| 0     | 0     | 0  | 0 (no press) | 1 (press)    | 1 (3 Pole) | 0 (4 Pole) | 0   |
| 0     | 1     | 0  | 0 (no press) | 0 (no press) | 1 (3 Pole) | 0 (4 Pole) | 0   |
| 0     | 0     | 1  | 0 (no press) | 1 (press)    | 1 (3 Pole) | 0 (4 Pole) | 0   |
| 1     | X     | X  | 0 (no press) | 0 (no press) | 1 (3 Pole) | 1 (3 Pole) | 1   |

**Note:**

3. State detected after initial plug-in.

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol              | Parameter                                                             |                                   | Min. | Max.         | Units |
|---------------------|-----------------------------------------------------------------------|-----------------------------------|------|--------------|-------|
| $V_{DD}$ & $V_{IO}$ | Supply Voltage from Battery                                           |                                   | -0.5 | 6.0          | V     |
| $V_{SW}$            | Switch I/O Voltage for “S” Switch and All Input Voltages Except J_DET |                                   | -0.5 | $V_{DD}+0.5$ | V     |
| $V_{JD}$            | Input Voltage for J_DET Input                                         |                                   | -1.5 | $V_{DD}+0.5$ | V     |
| $I_{IK}$            | Input Clamp Diode Current                                             |                                   | -50  |              | mA    |
| $I_{SW}$            | Switch I/O Current (Continuous)                                       |                                   |      | 50           | mA    |
| $T_{STG}$           | Storage Temperature Range                                             |                                   | -65  | +150         | °C    |
| $T_J$               | Maximum Junction Temperature                                          |                                   |      | +150         | °C    |
| $T_L$               | Lead Temperature (Soldering, 10 Seconds)                              |                                   |      | +260         | °C    |
| ESD                 | IEC 61000-4-2 System ESD                                              | Air Gap                           | 15.0 |              | kV    |
|                     |                                                                       | Contact                           | 8.0  |              |       |
|                     | JEDEC JESD22-A114, Human Body Model                                   | All Pins                          | 7.5  |              |       |
|                     |                                                                       | J_DET, J_MIC, $V_{DD}$ , $V_{IO}$ | 12.0 |              |       |
|                     | JEDEC JESD22-C101, Charged Device Model                               | All Pins                          | 2.0  |              |       |

**Note:**

- The input and output negative ratings may be exceeded if the input and output diode current ratings are observed.

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

| Symbol   | Parameter                   | Min. | Max.     | Units |
|----------|-----------------------------|------|----------|-------|
| $V_{DD}$ | Battery Supply Voltage      | 2.5  | 4.4      | V     |
| $V_{IO}$ | Parallel I/O Supply Voltage | 1.6  | $V_{DD}$ | V     |
| $T_A$    | Operating Temperature       | -40  | +85      | °C    |

## DC Electrical Characteristics

All typical values are at  $T_A = 25^\circ\text{C}$  unless otherwise specified.

| Symbol                  | Parameter                                                 | V <sub>DD</sub> (V) | Conditions                                                     | T <sub>A</sub> = -40 to +85°C |      |                       | Units |
|-------------------------|-----------------------------------------------------------|---------------------|----------------------------------------------------------------|-------------------------------|------|-----------------------|-------|
|                         |                                                           |                     |                                                                | Min.                          | Typ. | Max.                  |       |
| MIC Switch              |                                                           |                     |                                                                |                               |      |                       |       |
| R <sub>ON</sub>         | MIC Switch On Resistance                                  | 2.5                 | I <sub>OUT</sub> = 30 mA,<br>V <sub>IN</sub> = 2.0 V           |                               | 0.9  | 2.9                   | Ω     |
|                         |                                                           | 2.8                 |                                                                |                               | 0.8  | 2.5                   |       |
|                         |                                                           | 3.8                 |                                                                |                               | 0.6  | 2.0                   |       |
| R <sub>FLAT(ON)</sub>   | On Resistance Flatness                                    | 2.5                 | I <sub>OUT</sub> = 30 mA,<br>V <sub>IN</sub> = 1.6, 2.0, 2.5 V |                               | 1.50 |                       |       |
|                         |                                                           | 2.8                 | I <sub>OUT</sub> = 30 mA,<br>V <sub>IN</sub> = 1.6, 2.0, 2.8 V |                               | 0.70 |                       |       |
|                         |                                                           | 3.8                 |                                                                | 0.25                          |      |                       |       |
| V <sub>IN</sub>         | Switch Input Voltage Range                                | 2.5 to 4.4          |                                                                | 0                             |      | V <sub>DD</sub>       | V     |
| C <sub>ON</sub>         | MIC and J_MIC Switch ON Capacitance                       | 3.8                 | f = 1 MHz                                                      |                               | 76   |                       | pF    |
| C <sub>OFF</sub>        | MIC and J_MIC Switch OFF Capacitance                      | 3.8                 | f = 1 MHz                                                      |                               | 24   |                       | pF    |
| J_DET                   |                                                           |                     |                                                                |                               |      |                       |       |
| J_DET <sub>AudioV</sub> | Audio Voltage Range on J_DET Pin                          | 2.5 to 4.4          | DET = LOW                                                      | -1                            |      | 1                     | V     |
| J_DET <sub>Audiof</sub> | Audio Frequency on J_DET Pin                              | 2.5 to 4.4          | DET = LOW                                                      | 20                            |      | 20000                 | Hz    |
| J_DET <sub>RGND</sub>   | Detection Resistance to Ground                            | 2.5 to 4.4          | Audio Jack Inserted                                            | 0                             |      | 500                   | KΩ    |
| J_DET <sub>HYS</sub>    | Hysteresis of J_DET                                       |                     |                                                                |                               | 230  |                       | mV    |
| Parallel I/O            |                                                           |                     |                                                                |                               |      |                       |       |
| V <sub>IH</sub>         | Input High Voltage                                        |                     |                                                                | 0.7 x V <sub>IO</sub>         |      | V <sub>IO</sub>       | V     |
| V <sub>IL</sub>         | Input Low Voltage                                         |                     |                                                                |                               |      | 0.3 x V <sub>IO</sub> | V     |
| V <sub>OH</sub>         | Output High Voltage                                       |                     | I <sub>OH</sub> = -100 μA                                      | 0.8 x V <sub>IO</sub>         |      |                       | V     |
| V <sub>OL</sub>         | Output Low Voltage                                        |                     | I <sub>OL</sub> = +100 μA                                      |                               |      | 0.2 x V <sub>IO</sub> | V     |
| Comparator              |                                                           |                     |                                                                |                               |      |                       |       |
| V <sub>COMP</sub>       | Comparator Threshold for SEND/END Sensing                 | 2.5-3.8             | J_DET, EN = LOW                                                |                               | 620  |                       | mV    |
| Current                 |                                                           |                     |                                                                |                               |      |                       |       |
| I <sub>OFF</sub>        | Power Off Leakage Current Through Switch                  | 0                   | MIC and J_MIC Ports V <sub>IN</sub> = 4.4 V                    |                               |      | 1.5                   | μA    |
| I <sub>IN</sub>         | Input Leakage Current                                     | 0 to 4.4            | Inputs 0 = 4.4 V                                               |                               |      | 1                     | μA    |
| I <sub>CC-SLNA</sub>    | Battery Supply Sleep Mode Current No Accessory Attached   | 2.5 to 4.4          | Static Current During Sleep Mode (EN = LOW)                    |                               | 1    | 3                     | μA    |
| I <sub>CC-SLWA</sub>    | Battery Supply Sleep Mode Current with Accessory Attached | 2.5 to 4.4          | Active Current (EN = LOW and/or DET = HIGH)                    |                               | 15   | 25                    | μA    |


## AC Electrical Characteristics

All typical values are for  $V_{CC}=3.3\text{ V}$  at  $T_A=25^\circ\text{C}$  unless otherwise specified.


| Symbol                          | Parameter                                                                            | V <sub>DD</sub> (V) | Conditions                                                                                                         | T <sub>A</sub> = -40 to +85°C |      |      | Unit |
|---------------------------------|--------------------------------------------------------------------------------------|---------------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------|------|------|------|
|                                 |                                                                                      |                     |                                                                                                                    | Min.                          | Typ. | Max. |      |
| MIC Switch                      |                                                                                      |                     |                                                                                                                    |                               |      |      |      |
| THD                             | Total Harmonic Distortion                                                            | 3.8                 | R <sub>T</sub> = 600 Ω, V <sub>SW</sub> = 0.5 V <sub>PP</sub> ,<br>f = 20 Hz to 20 kHz,<br>V <sub>IN</sub> = 2.0 V |                               | 0.01 |      | %    |
| O <sub>IRR</sub>                | Off Isolation                                                                        | 3.8                 | f = 20 kHz, R <sub>S</sub> = 32 Ω,<br>C <sub>L</sub> = 0 pF, R <sub>T</sub> = 32 Ω                                 |                               | -90  |      | dB   |
| Parallel I/O                    |                                                                                      |                     |                                                                                                                    |                               |      |      |      |
| t <sub>R</sub> , t <sub>F</sub> | Output Edge Rates (DET, S/E, JPOLE)                                                  | 2.5                 | C <sub>L</sub> = 5 pF, 20% to 80%                                                                                  |                               | 19   |      | ns   |
|                                 |                                                                                      | 3.8                 |                                                                                                                    |                               | 15   |      |      |
| t <sub>POLL</sub>               | On Time of MIC Switch for Sensing<br>SEND/END Button Press Oscillator<br>Stable Time | 2.5 to 4.4          |                                                                                                                    |                               | 1    |      | ms   |
| t <sub>PER</sub>                | Period of MIC Switching Time for<br>Sensing SEND/END Button Press                    | 2.5 to 4.4          |                                                                                                                    |                               | 10   |      | ms   |
| t <sub>DET-IN</sub>             | Debounce Time after J-DET Changes<br>State from High to Low                          | 2.5 to 4.4          |                                                                                                                    |                               | 422  |      | ms   |
| t <sub>DET-REM</sub>            | Debounce Time after J_DET Changes<br>State from Low to High                          | 2.5 to 4.4          |                                                                                                                    |                               | 30   |      | μs   |
| t <sub>DET</sub>                | Detection Timeout for Sensing 3-Pole<br>or 4-Pole Audio Jack Plugged In              | 2.5 to 4.4          |                                                                                                                    |                               | 4.5  |      | ms   |
| t <sub>KBK</sub>                | Debounce Time for Sensing<br>SEND/END Key Press / Release                            | 2.5 to 4.4          |                                                                                                                    |                               | 27   |      | ms   |
| Power                           |                                                                                      |                     |                                                                                                                    |                               |      |      |      |
| PSRR                            | Power Supply Rejection Ratio                                                         | 3.8                 | Power Supply Noise<br>300 mV <sub>PP</sub> , Measured<br>10/90%, f = 217 Hz                                        |                               | -90  |      | dB   |

**Table 4. Package Nominal Values**


| JEDEC Symbol | Description      | Nominal Values (mm) |
|--------------|------------------|---------------------|
| A            | Overall Height   | 0.5                 |
| A1           | Package Standoff | 0.072               |
| A3           | Lead Thickness   | 0.152               |
| b            | Lead Width       | 0.4                 |
| L            | Lead Length      | 0.2                 |
| e            | Lead Pitch       | 0.4                 |
| D            | Body Length (Y)  | 1.8                 |
| E            | Body Width (X)   | 1.4                 |




TOP VIEW




SIDE VIEW



BOTTOM VIEW




DETAIL A  
SCALE : 2X




LEAD  
OPTION 1  
SCALE : 2X

LEAD  
OPTION 2  
SCALE : 2X



RECOMMENDED LAND PATTERN



OPTIONAL MINIMAL  
TOE LAND PATTERN

#### NOTES:

- PACKAGE DOES NOT CONFORM TO ANY JEDEC STANDARD.
- DIMENSIONS ARE IN MILLIMETERS.
- LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.
- DRAWING FILENAME: MKT-UMLP10ArevG.

ON Semiconductor



ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative