



Dual Power HiPerFET™ Module

VMM 300-03F

$V_{DSS} = 300\text{ V}$
 $I_{D25} = 290\text{ A}$
 $R_{DS(on) \text{ typ.}} = 7.4\text{ m}\Omega$

Phaseleg Configuration
 High dv/dt, Low t_{rr} , HDMOS™ Family



Symbol	Conditions	Maximum Ratings	
V_{DSS}	$T_J = 25^\circ\text{C to } 150^\circ\text{C}$	300	V
V_{DGR}	$T_J = 25^\circ\text{C to } 150^\circ\text{C}; R_{GS} = 10\text{ k}\Omega$	300	V
V_{GS}	Continuous	± 20	V
V_{GSM}	Transient	± 30	V
I_{D25}	$T_C = 25^\circ\text{C}$	290	A
I_{D80}	$T_C = 80^\circ\text{C}$	220	A
I_{DM}	$T_C = 25^\circ\text{C}; t_p = 10\text{ }\mu\text{s}$ ①	1160	A
P_D	$T_C = 25^\circ\text{C}$	1500	W
T_J		-40 ... +150	$^\circ\text{C}$
T_{JM}		150	$^\circ\text{C}$
T_{stg}		-40 ... +125	$^\circ\text{C}$
V_{ISOL}	50/60 Hz $I_{ISOL} \leq 1\text{ mA}$	$t = 1\text{ min}$ $t = 1\text{ s}$	3000 3600 V~
M_d	Mounting torque (M6) Terminal connection torque (M5)	2.25-2.75/20-25 2.5-3.7/22-33	Nm/lb.in. Nm/lb.in.
Weight	typical including screws	250	g

Features

- Low $R_{DS(on)}$ HDMOS™ process
- International standard package
- Low package inductance for high speed switching
- Kelvin Source contact for easy drive
- **Direct Copper Bonded** Al_2O_3 ceramic base plate

Applications

- AC motor speed control for electric vehicles
- DC servo and robot drives
- Switched-mode and resonant-mode power supplies
- DC choppers

Advantages

- Easy to mount
- Space and weight savings
- High power density
- Low losses

Symbol	Conditions	Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
V_{DSS}	$V_{GS} = 0\text{ V}, I_D = 12\text{ mA}$	300		V
$V_{GS(th)}$	$V_{DS} = 20\text{ V}, I_D = 30\text{ mA}$	2		V
I_{GSS}	$V_{GS} = \pm 20\text{ V DC}, V_{DS} = 0$			$\pm 500\text{ nA}$
I_{DSS}	$V_{DS} = V_{DSS}$ $V_{GS} = 0\text{ V}$			$T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$ 0.5 mA 8 mA
$R_{DS(on)}$	$V_{GS} = 10\text{ V}, I_D = 0.5 \cdot I_{D25}$ Pulse test, $t \leq 300\text{ }\mu\text{s}$, duty cycle $d \leq 2\%$		7.4	8.6 m Ω

① Additional current limitation by external leads

IXYS reserves the right to change limits, test conditions and dimensions.

Symbol	Conditions	Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
g_{fs}	$V_{DS} = 10\text{ V}; I_D = 0.5 \cdot I_{D25}$ pulsed		280	S
C_{iss}	$V_{GS} = 0\text{ V}, V_{DS} = 25\text{ V}, f = 1\text{ MHz}$		40	nF
C_{oss}			7.2	nF
C_{rss}			2.8	nF
$t_{d(on)}$	$V_{GS} = 10\text{ V}, V_{DS} = 0.5 \cdot V_{DSS}, I_D = 0.5 \cdot I_{D25}$ $R_G = 1\ \Omega$		200	ns
t_r			400	ns
$t_{d(off)}$			400	ns
t_f			150	ns
Q_g	$V_{GS} = 10\text{ V}, V_{DS} = 150\text{ V}, I_D = 150\text{ A}$		1440	nC
Q_{gs}			240	nC
Q_{gd}			720	nC
R_{thJC}	with heat transfer paste			0.08 K/W
R_{thJS}			0.12	K/W

Source-Drain Diode

Symbol	Conditions	Characteristic Values ($T_J = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
I_S	$V_{GS} = 0\text{ V}, T_C = 25^\circ\text{C}, T_J = T_{JM}$			290 A
I_{SM}	②			1160 A
V_{SD}	$I_F = 300\text{ A}, V_{GS} = 0\text{ V},$ Pulse test, $t \leq 300\ \mu\text{s}$, duty cycle $d \leq 2\%$		0.9	1.1 V
t_{rr}	$I_F = 300\text{ A}, -di/dt = 400\text{ A}/\mu\text{s}, V_{DS} = 0.5 \cdot V_{DSS}$		300	ns

② Additional current limitation by external leads

