

S1V30080


♪Melody Synthesizer♪ function included Voice Guidance LSI

■ Outline

S1V30080 supports multi-channel Speech/Sound playback from integrated ROM, Moreover Melody Synthesizer function is supported which is suitable for music effect and buzzer sound by tiny data with Speech/Sound playback. Speech/Sound playback and melody synthesizer function works individually and can be mixed, of course the volume can be set individually.

The voice data creation tool for EPSON voice guidance LSI allows easy creation of high-quality voice data from text data without studio recording.

S1V30080 is controlled over the serial interface allowing control from a wide range of hosts easily from the host and also S1V30080 supports standalone mode which enable to control without CPU or without host S/W on CPU.



■ Features

● Melody/Buzzer/Tone sound synthesizer function

- 5-ch Melody Sound can be created just by music note information(5 octave supported)
- Buzzer/Tone Sound can be generated just by specifying the frequency(5ch supported)

● Speech/Sound Playback

- Individual 2ch Voice ROM data can be played.(EPSON original format)
- Sampling Frequency : 4, 8, 12 and 16 kHz

● Sequencer function (to set delay between phrases)

- A maximum of 127 files can be sequenced with one configuration message (no constraints on phrase combinations)
- Delay setting can be set between phrases: 0-1000ms (10ms step)

● Mixing Function

- Synthesizer Sound and Speech/Sound Playback from ROM can be mixed(individual volume setting possible)

● Speech/Sound ROM

- fs:8kHz approx 30 sec, fs:16kHz approx 15sec

● Host Interface

- Synchronous serial interface (SPI, I2C) ... [Command Control base]

● Standalone mode

- By just specifying the ruled number, the sound can be played from ROM and Melody Synthesizer.

● DA Converter integrated

● Clock(Crystal oscillation, Ceramic oscillation, Clock input

- fs:8kHz 8.192MHz, fs:16kHz 16.384MHz

● Power Supply voltage

- 2.2-5.5V Single Power Supply

● Product Configuration


Product code	System clock source	Package
S1V30080F00**00	External clock	QFP12-48 (7mm x 7mm, 0.5mm pin pitch)
S1V30080F10**00	External clock	QFP13-52 (10mm x 10mm, 0.65mm pin pitch)
S1V30080F11**00	crystal unit	QFP13-52 (10mm x 10mm, 0.65mm pin pitch)

S1V30080


■ Standard Application System

The S1V30080 standard application system will have the following configuration. The host processor will control the S1V30080 device by commands sent via the serial interface (the message protocol).

In addition, S1V30080 supports standalone mode which enable to control without CPU or without host S/W on CPU.




Serial Interface Mode




Standalone Mode

■ Standard Application System

- Evaluation Board
- Voice Data Creation Tool(Supported languages: English, Japanese, Korean (all female voices))
- Melody/Buzzer/Tone Synthesizer Creation Tool
- Sample Program



Voice Data Creation Tool(PC software tool)



Melody/Buzzer/Tone Synthesizer Creation Tool(PC software tool)

NOTICE:

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You are requested not to use, to resell, to export and/or to otherwise dispose of the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.
©Seiko Epson Corporation 2015, All rights reserved

SEIKO EPSON CORPORATION

MICRODEVICES OPERATIONS DIVISION

EPSON semiconductor website

<http://global.epson.com/products/semicon/>

Device Sales & Marketing Department
421-8 Hino, Hino-shi, Tokyo 191-8501, JAPAN
Phone: +81-42-587-5814 FAX: +81-42-587-5117

Document code: 411698002
First issue February, 2009
Revised June, 2015 in Japan