



# Hittite MICROWAVE PRODUCTS FROM ANALOG DEVICES

# Analog Devices Welcomes Hittite Microwave Corporation

**NO CONTENT ON THE ATTACHED DOCUMENT HAS CHANGED**



**THIS PAGE INTENTIONALLY LEFT BLANK**

## Typical Applications


The HMC474SC70(E) is an ideal for:

- Cellular / PCS / 3G
- WiBro / WiMAX / 4G
- Fixed Wireless & WLAN
- CATV, Cable Modem & DBS
- Microwave Radio & Test Equipment

## Features

- Gain: 15 dB
- P1dB Output Power: +8 dBm
- Output IP3: +20 dBm
- Cascadable 50 Ohm I/Os
- Single Supply: +3V to +10V
- Industry Standard SC70 Package

## Functional Diagram



## General Description

The HMC474SC70(E) is a general purpose SiGe Heterojunction Bipolar Transistor (HBT) Gain Block MMIC SMT amplifier covering DC to 6 GHz. This industry standard SC70 packaged amplifier can be used as a cascadable 50 Ohm RF/IF gain stage with up to +8 dBm output power. The HMC474SC70(E) offers 15 dB of gain with a +20 dBm output IP3 at 850 MHz while requiring only 25 mA from a single positive supply as low as +3V. The Darlington topology results in reduced sensitivity to normal process variations and excellent gain stability over temperature while requiring a minimal number of external bias components.

## Electrical Specifications, Vs= 5V, Rbias= 110 Ohm, TA = +25° C

Parameter	Min.	Typ.	Max.	Units
Gain	DC - 2.0 GHz 2.0 - 4.0 GHz 4.0 - 6.0 GHz	12 10 7	15 13 10	dB dB dB
Gain Variation Over Temperature	DC - 6 GHz		0.01	0.015
dB/ °C				
Input Return Loss	DC - 5 GHz 5.0 - 6.0 GHz		15 14	dB dB
Output Return Loss	DC - 5 GHz 5.0 - 6.0 GHz		15 12	dB dB
Reverse Isolation	DC - 6 GHz		17	dB
Output Power for 1 dB Compression (P1dB)	0.5 - 4.0 GHz 5.0 - 6.0 GHz	5 3	8 6	dBm dBm
Output Third Order Intercept (IP3) (Pout= 0 dBm per tone, 1 MHz spacing)	DC - 5 GHz 5.0 - 6.0 GHz		20 18	dBm dBm
Noise Figure	DC - 5 GHz 5.0 - 6.0 GHz		3 3.9	dB dB
Supply Current (Icq)			25 33	mA


Note: Data taken with broadband bias tee on device output.

For price, delivery and to place orders: Analog Devices, Inc., 20 Alpha Road, Chelmsford, MA 01824


Phone: 978-250-3343 • Fax: 978-250-3373 • Order On-line at [www.hittite.com](http://www.hittite.com)

Application Support: Phone: 978-250-3343 or [apps@hittite.com](mailto:apps@hittite.com)


**Broadband Gain & Return Loss**




**Gain vs. Temperature**




**Input Return Loss vs. Temperature**




**Output Return Loss vs. Temperature**








**Reverse Isolation vs. Temperature**



**Noise Figure vs. Temperature**



**P1dB vs. Temperature****Psat vs. Temperature****Output IP3 vs. Temperature****Gain, Power & OIP3 vs. Supply Voltage for  $R_s = 110$  Ohms @ 850 MHz****Icc vs. Vcc Over Temperature for Fixed Vs= 5V, R<sub>BIAS</sub>= 110 Ohms**


### Absolute Maximum Ratings

Collector Bias Voltage (Vcc)	+6.0 Vdc
Collector Bias Current (Icc)	35 mA
RF Input Power (RFIN)(Vcc = +2.4 Vdc)	+5 dBm
Junction Temperature	150 °C
Continuous Pdiss (T = 85 °C) (derate 4.3 mW/°C above 85 °C)	0.280 W
Thermal Resistance (junction to lead)	232 °C/W
Storage Temperature	-65 to +150 °C
Operating Temperature	-40 to +85 °C
ESD Sensitivity (HBM)	Class 1B



ELECTROSTATIC SENSITIVE DEVICE  
OBSERVE HANDLING PRECAUTIONS

### Outline Drawing



#### NOTES:

1. PACKAGE BODY MATERIAL: LOW STRESS INJECTION MOLDED PLASTIC SILICA AND SILICON IMPREGNATED.
2. LEAD MATERIAL: COPPER ALLOY
3. LEAD PLATING: Sn/Pb
4. DIMENSIONS ARE IN INCHES [MILLIMETERS].
5. DIMENSION DOES NOT INCLUDE MOLDFLASH OF 0.15mm PER SIDE.
6. DIMENSION DOES NOT INCLUDE MOLDFLASH OF 0.25mm PER SIDE.
7. ALL GROUND LEADS MUST BE SOLDERED TO PCB RF GROUND.


### Package Information

Part Number	Package Body Material	Lead Finish	MSL Rating	Package Marking
HMC474SC70	Low Stress Injection Molded Plastic	Sn/Pb	MSL1 <sup>[1]</sup>	474E
HMC474SC70E	RoHS-compliant Low Stress Injection Molded Plastic	100% matte Sn	MSL1 <sup>[2]</sup>	474E


[1] Max peak reflow temperature of 235 °C

[2] Max peak reflow temperature of 260 °C

### Pin Descriptions

Pin Number	Function	Description	Interface Schematic
1, 2, 4, 5	GND	These pins must be connected to RF/DC ground.	
3	RFIN	This pin is DC coupled. An off chip DC blocking capacitor is required.	
6	RFOUT	RF output and DC Bias (Vcc) for the output stage.	

### Application Circuit



### Recommended Bias Resistor Values for $I_{cc} = 25$ mA, $R_{bias} = (Vs - Vcc) / I_{cc}$

Supply Voltage (Vs)	3V	5V	6V	8V	10V
$R_{bias}$ VALUE	30 Ω	110 Ω	150 Ω	240 Ω	300 Ω
$R_{bias}$ POWER RATING	1/8 W	1/8 W	1/4 W	1/2 W	1/2 W

#### Note:

1. External blocking capacitors are required on RFIN and RFOUT.
2.  $R_{bias}$  provides DC bias stability over temperature.

### Recommended Component Values for Key Application Frequencies


Component	Frequency (MHz)							
	50	900	1900	2200	2400	3500	5200	5500
L1	270 nH	56 nH	18 nH	18 nH	15 nH	8.2 nH	6.8 nH	3.3 nH
C1, C2	0.01 μF	100 pF						

For price, delivery and to place orders: Analog Devices, Inc., 20 Alpha Road, Chelmsford, MA 01824

Phone: 978-250-3343 • Fax: 978-250-3373 • Order On-line at [www.hittite.com](http://www.hittite.com)

Application Support: Phone: 978-250-3343 or [apps@hittite.com](mailto:apps@hittite.com)

**Evaluation PCB**



**List of Materials for Evaluation PCB 117596<sup>[1]</sup>**

Item	Description
J1 - J2	PCB Mount SMA Connector
J3 - J4	DC Pin
C1 - C3	100 pF Capacitor, 0402 Pkg.
C4	1000 pF Capacitor, 0603 Pkg.
C5	2.2 $\mu$ F Capacitor, Tantalum
R1	110 Ohm Resistor, 1210 Pkg.
L1	18 nH Inductor, 0603 Pkg.
U1	HMC474SC70(E)
PCB <sup>[2]</sup>	117360 Evaluation PCB

The circuit board used in the application should use RF circuit design techniques. Signal lines should have 50 Ohm impedance while the package ground leads should be connected directly to the ground plane similar to that shown. A sufficient number of via holes should be used to connect the top and bottom ground planes. The evaluation board should be mounted to an appropriate heat sink. The evaluation circuit board shown is available from Hittite upon request.

[1] Reference this number when ordering complete evaluation PCB

[2] Circuit Board Material: Rogers 4350