





## Optocoupler, Phototransistor Output, AC Input, with Base Connection



i179037-1



### FEATURES

- AC or polarity insensitive inputs
- Built-in reverse polarity input protection
- Improved CTR symmetry
- Industry standard DIP package
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### APPLICATIONS

- Ideal for AC signal detection and monitoring

### AGENCY APPROVALS

- UL1577, file no. E52744, double protection
- cUL tested to CSA 22.2 bulletin 5A
- CSA 93751
- BSI EN 60950, BSI EN 60065
- DIN EN 60747-5-5 (VDE 0884-5)
- CQC GB4943.1-2011 and GB8898-2011 (suitable for installation altitude below 2000 m)



### DESCRIPTION

The IL250, IL251, IL252, ILD252 are bidirectional input optically coupled isolators consisting of two gallium arsenide infrared LEDs coupled to a silicon NPN phototransistor per channel.

The IL250 has a minimum CTR of 50 %, the IL251 has a minimum CTR of 20 %, and the IL252, ILD252 has a minimum CTR of 100 %.

The IL250, IL251, IL252 are single channel optocouplers. The ILD252 has two isolated channels in a single DIP package.

### ORDERING INFORMATION



| AGENCY CERTIFIED/PACKAGE      | CTR (%)               |                            |                            |                     |
|-------------------------------|-----------------------|----------------------------|----------------------------|---------------------|
|                               | SINGLE CHANNEL, 6 PIN |                            |                            | DUAL CHANNEL, 8 PIN |
| <b>UL, CSA, BSI, CQC</b>      | ≥ 20                  | ≥ 50                       | ≥ 100                      | ≥ 100               |
| DIP-#                         | IL251                 | IL250                      | IL252                      | -                   |
| SMD-#, option 7               | -                     | IL250-X007                 | IL252-X007T <sup>(1)</sup> | -                   |
| SMD-#, option 9               | IL251-X009T           | IL250-X009T <sup>(1)</sup> | IL252-X009T <sup>(1)</sup> | -                   |
| <b>VDE, UL, CSA, BSI, CQC</b> | ≥ 20                  | ≥ 50                       | ≥ 100                      | ≥ 100               |
| DIP-#                         | -                     | IL250-X001                 | IL252-X001                 | -                   |
| DIP-#, option 6               | -                     | -                          | IL252-X016                 | -                   |
| SMD-#, option 7               | -                     | -                          | IL252-X017T <sup>(1)</sup> | ILD252-X017         |

#### Notes

- Additional options may be possible, please contact sales office
- <sup>(1)</sup> Also available in tubes; do not add "T" to end



| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                |            |             |       |
|--------------------------------------------------------------------------------------------------------|----------------|------------|-------------|-------|
| PARAMETER                                                                                              | TEST CONDITION | SYMBOL     | VALUE       | UNIT  |
| <b>INPUT</b>                                                                                           |                |            |             |       |
| Forward continuous current                                                                             |                | $I_F$      | 60          | mA    |
| Power dissipation                                                                                      |                | $P_{diss}$ | 100         | mW    |
| Derate linearly from 25 °C                                                                             |                |            | 1.33        | mW/°C |
| <b>OUTPUT</b>                                                                                          |                |            |             |       |
| Collector emitter breakdown voltage                                                                    |                | $BV_{CEO}$ | 30          | V     |
| Emitter base breakdown voltage                                                                         |                | $BV_{EBO}$ | 5           | V     |
| Collector base breakdown voltage                                                                       |                | $BV_{CBO}$ | 70          | V     |
| Power dissipation single channel                                                                       |                | $P_{diss}$ | 200         | mW    |
| Power dissipation dual channel                                                                         |                | $P_{diss}$ | 150         | mW    |
| Derate linearly from 25 °C single channel                                                              |                |            | 2.6         | mW/°C |
| Derate linearly from 25 °C dual channel                                                                |                |            | 2           | mW/°C |
| <b>COUPLER</b>                                                                                         |                |            |             |       |
| Total dissipation single channel                                                                       |                | $P_{tot}$  | 250         | mW    |
| Total dissipation dual channel                                                                         |                | $P_{tot}$  | 400         | mW    |
| Derate linearly from 25 °C single channel                                                              |                |            | 3.3         | mW/°C |
| Derate linearly from 25 °C dual channel                                                                |                |            | 5.3         | mW/°C |
| Storage temperature                                                                                    |                | $T_{stg}$  | -55 to +150 | °C    |
| Operating temperature                                                                                  |                | $T_{amb}$  | -55 to +100 | °C    |
| Lead soldering time at 260 °C                                                                          |                |            | 10          | s     |

**Note**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability

| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                |             |      |      |      |      |
|----------------------------------------------------------------------------------------------------------|------------------------------------------------|-------------|------|------|------|------|
| PARAMETER                                                                                                | TEST CONDITION                                 | SYMBOL      | MIN. | TYP. | MAX. | UNIT |
| <b>INPUT</b>                                                                                             |                                                |             |      |      |      |      |
| Forward voltage                                                                                          | $I_F = \pm 10\text{ mA}$                       | $V_F$       | -    | 1.2  | 1.5  | V    |
| <b>OUTPUT</b>                                                                                            |                                                |             |      |      |      |      |
| Collector emitter breakdown voltage                                                                      | $I_C = 1\text{ mA}$                            | $BV_{CEO}$  | 30   | 50   | -    | V    |
| Emitter base breakdown voltage                                                                           | $I_E = 100\text{ }\mu\text{A}$                 | $BV_{EBO}$  | 7    | 10   | -    | V    |
| Collector base breakdown voltage                                                                         | $I_C = 10\text{ }\mu\text{A}$                  | $BV_{CBO}$  | 70   | 90   | -    | V    |
| Collector emitter leakage current                                                                        | $V_{CE} = 10\text{ V}$                         | $I_{CEO}$   | -    | 5    | 50   | nA   |
| <b>COUPLER</b>                                                                                           |                                                |             |      |      |      |      |
| Collector emitter saturation voltage                                                                     | $I_F = \pm 16\text{ mA}$ , $I_C = 2\text{ mA}$ | $V_{CEsat}$ | -    | -    | 0.4  | V    |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements

**CURRENT TRANSFER RATIO** ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)

| PARAMETER | TEST CONDITION                                    | PART          | SYMBOL     | MIN. | TYP. | MAX. | UNIT |
|-----------|---------------------------------------------------|---------------|------------|------|------|------|------|
| $I_C/I_F$ | $I_F = \pm 10\text{ mA}$ , $V_{CE} = 10\text{ V}$ | IL250         | $CTR_{DC}$ | 50   | -    | -    | %    |
|           |                                                   | IL251         | $CTR_{DC}$ | 20   | -    | -    | %    |
|           |                                                   | IL252, ILD252 | $CTR_{DC}$ | 100  | -    | -    | %    |
| Symmetry  | $I_F = \pm 10\text{ mA}$                          |               |            | 0.50 | 1    | 2    |      |

**SWITCHING CHARACTERISTICS** ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)

| PARAMETER     | TEST CONDITION | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
|---------------|----------------|-----------|------|------|------|---------------|
| Turn-on time  |                | $t_{on}$  | -    | TBD  | -    | $\mu\text{s}$ |
| Turn-off time |                | $t_{off}$ | -    | TBD  | -    | $\mu\text{s}$ |

**SAFETY AND INSULATION RATINGS**

| PARAMETER                                    | TEST CONDITION                                      | SYMBOL     | VALUE          | UNIT               |
|----------------------------------------------|-----------------------------------------------------|------------|----------------|--------------------|
| Climatic classification                      | According to IEC 68 part 1                          |            | 55/100/21      |                    |
| Comparative tracking index                   |                                                     | CTI        | 175            |                    |
| Maximum rated withstanding isolation voltage | $t = 1\text{ min}$                                  | $V_{ISO}$  | 4420           | $V_{RMS}$          |
| Maximum transient isolation voltage          |                                                     | $V_{IOTM}$ | 10 000         | $V_{peak}$         |
| Maximum repetitive peak isolation voltage    |                                                     | $V_{IORM}$ | 890            | $V_{peak}$         |
| Isolation resistance                         | $V_{IO} = 500\text{ V}$ , $T_{amb} = 25\text{ °C}$  | $R_{IO}$   | $\geq 10^{12}$ | $\Omega$           |
|                                              | $V_{IO} = 500\text{ V}$ , $T_{amb} = 100\text{ °C}$ | $R_{IO}$   | $\geq 10^{11}$ | $\Omega$           |
| Output safety power                          |                                                     | $P_{SO}$   | 400            | mW                 |
| Input safety current                         |                                                     | $I_{SI}$   | 275            | mA                 |
| Safety temperature                           |                                                     | $T_S$      | 175            | $^{\circ}\text{C}$ |
| Creepage distance                            |                                                     |            | $\geq 7$       | mm                 |
| Clearance distance                           |                                                     |            | $\geq 7$       | mm                 |
| Insulation thickness                         |                                                     | DTI        | $\geq 0.4$     | mm                 |

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits


**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 1 - LED Forward Current vs. Forward Voltage




Fig. 4 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 2 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 5 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 3 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 6 - Collector Emitter Current vs. Temperature and LED Current




Fig. 7 - Collector Emitter Leakage Current vs. Temperature







Fig. 10 - Normalized Photocurrent vs.  $I_F$  and Temperature

Fig. 8 - Normalized  $CTR_{CB}$  vs. LED Current and Temperature

Fig. 11 - Normalized Non Saturated  $h_{FE}$  vs. Base Current and Temperature


Fig. 9 - Collector Base Photocurrent vs. LED Current


Fig. 12 - Normalized Saturated  $h_{FE}$  vs. Base Current and Temperature




Fig. 13 - Propagation Delay vs. Collector Load Resistor




Fig. 14 - Switching Timing















Fig. 15 - Switching Schematic



## PACKAGE DIMENSIONS in inches (millimeters)



18450



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.