



Dual N-Channel 30-V (D-S) MOSFET with Schottky Diode

PRODUCT SUMMARY

	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)
Channel-1	30	0.022 at V _{GS} = 10 V	6.3
		0.030 at V _{GS} = 4.5 V	5.4
Channel-2		0.0155 at V _{GS} = 10 V	9.5
		0.0205 at V _{GS} = 4.5 V	8.2

SCHOTTKY PRODUCT SUMMARY



V _{DS} (V)	V _{SD} (V) Diode Forward Voltage	I _F (A)
30	0.50 V at 1.0 A	2.0

FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- LITTLE FOOT® Plus
- Compliant to RoHS directive 2002/95/EC



RoHS
COMPLIANT
HALOGEN
FREE
Available



Ordering Information: Si4818DY-T1-E3 (Lead (Pb)-free)
Si4818DY-T1-GE3 (Lead (Pb)-free and Halogen-free)

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter		Symbol	Channel-1		Channel-2		Unit
			10 s	Steady State	10 s	Steady State	
Drain-Source Voltage		V _{DS}	30				V
Gate-Source Voltage		V _{GS}	20				
Continuous Drain Current (T _J = 150 °C) ^a	T _A = 25 °C	I _D	6.3	5.3	9.5	7.0	A
	T _A = 70 °C		5.4	4.2	7.6	5.6	
Pulsed Drain Current		I _{DM}	30		40		
Continuous Source Current (Diode Conduction) ^a		I _S	1.3	0.9	2.2	1.15	
Maximum Power Dissipation ^a	T _A = 25 °C	P _D	1.4	1.0	2.4	1.25	W
	T _A = 70 °C		0.9	0.64	1.5	0.80	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150				°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Channel-1		Channel-2		Schottky		Unit
		Typ.	Max.	Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^a	R _{thJA}	72	90	43	53	48	60	°C/W
		100	125	82	100	80	100	
Maximum Junction-to-Foot (Drain)	R _{thJC}	51	63	25	30	28	35	

Notes:

a. Surface Mounted on 1" x 1" FR4 board.

MOSFET SPECIFICATIONS T _J = 25 °C, unless otherwise noted								
Parameter	Symbol	Test Conditions		Min.	Typ. ^a	Max.	Unit	
Static								
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	Ch-1 Ch-2	0.8 1.0			V	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = 20 V	Ch-1 Ch-2			100 100	nA	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 24 V, V _{GS} = 0 V	Ch-1			1	μA	
			Ch-2			100		
		V _{DS} = 24 V, V _{GS} = 0 V, T _J = 85 °C	Ch-1			15		
			Ch-2			2000		
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	Ch-1 Ch-2	20 30			A	
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 10 V, I _D = 6.3 A	Ch-1		0.018	0.022	Ω	
		V _{GS} = 10 V, I _D = 9.5 A	Ch-2		0.0125	0.0155		
		V _{GS} = 4.5 V, I _D = 5.4 A	Ch-1		0.024	0.030		
		V _{GS} = 4.5 V, I _D = 8.2 A	Ch-2		0.0165	0.0205		
Forward Transconductance ^b	g _{fs}	V _{DS} = 15 V, I _D = 6.3 A	Ch-1		17		S	
		V _{DS} = 15 V, I _D = 9.5 A	Ch-2		28			
Diode Forward Voltage ^b	V _{SD}	I _S = 1.3 A, V _{GS} = 0 V	Ch-1		0.7	1.1	V	
		I _S = 1 A, V _{GS} = 0 V	Ch-2		0.47	0.5		
Dynamic ^a								
Total Gate Charge	Q _g	Channel-1 V _{DS} = 15 V, V _{GS} = 5 V, I _D = 6.3 A	Ch-1 Ch-2		8.0 15	12 23	nC	
Gate-Source Charge	Q _{gs}		Ch-1 Ch-2		1.75 5.3			
Gate-Drain Charge	Q _{gd}	Channel-2 V _{DS} = 15 V, V _{GS} = 5 V, I _D = - 9.5 A	Ch-1 Ch-2		3.2 4.6			
			Ch-1 Ch-2					
Gate Resistance	R _g		Ch-1 Ch-2	1.5 0.5		6.1 2.6	Ω	
Turn-On Delay Time	t _{d(on)}	Channel-1 V _{DD} = 15 V, R _L = 15 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 6 Ω	Ch-1 Ch-2		10 15	20 30	ns	
Rise Time	t _r		Ch-1 Ch-2		5 5	10 10		
Turn-Off Delay Time	t _{d(off)}		Channel-2 V _{DD} = 15 V, R _L = 15 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 6 Ω	Ch-1 Ch-2		26 44		50 80
				Ch-1 Ch-2		8 12		16 24
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 1.3 A, dI/dt = 100 A/μs	Ch-1		30	60		
		I _F = 2.2 A, dI/dt = 100 μA/μs	Ch-2		32	70		

Notes:

a. Guaranteed by design, not subject to production testing.


b. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$.

SCHOTTKY SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted						
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward Voltage Drop	V_F	$I_F = 1.0\ \text{A}$		0.47	0.50	V
		$I_F = 1.0\ \text{A}$, $T_J = 125^\circ\text{C}$		0.36	0.42	
Maximum Reverse Leakage Current	I_{rm}	$V_R = 30\ \text{V}$		0.004	0.100	mA
		$V_R = 30\ \text{V}$, $T_J = 100^\circ\text{C}$		0.7	10	
		$V_R = -30\ \text{V}$, $T_J = 125^\circ\text{C}$		3.0	20	
Junction Capacitance	C_T	$V_R = 10\ \text{V}$		50		pF


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current








Capacitance



Gate Charge




On-Resistance vs. Junction Temperature

CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Source-Drain Diode Forward Voltage****On-Resistance vs. Gate-to-Source Voltage****Threshold Voltage****Single Pulse Power, Junction-to-Ambient****Normalized Thermal Transient Impedance, Junction-to-Ambient**




CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Foot


CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics









Transfer Characteristics



On-Resistance vs. Drain Current




Capacitance


CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Gate Charge****On-Resistance vs. Junction Temperature****Source-Drain Diode Forward Voltage****On-Resistance vs. Gate-to-Source Voltage****Threshold Voltage****Single Pulse Power, Junction-to-Ambient**




CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot

SCHOTTKY TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Reverse Current vs. Junction Temperature



Forward Voltage Drop





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.