



Quad N-Channel 30-V (D-S) MOSFETs

PRODUCT SUMMARY				
Part Number	$V_{(BR)DSS}$ Min (V)	$r_{DS(on)}$ Max (Ω)	$V_{GS(th)}$ (V)	I_D (A)
VQ1001J	30	1 @ $V_{GS} = 12$ V	0.8 to 2.5	0.83
VQ1001P		1 @ $V_{GS} = 12$ V	0.8 to 2.5	0.53

FEATURES


- Low On-Resistance: 0.85 Ω
- Low Threshold: 1.4 V
- Low Input Capacitance: 38 pF
- Fast Switching Speed: 9 ns
- Low Input and Output Leakage

BENEFITS

- Low Offset Voltage
- Low-Voltage Operation
- Easily Driven Without Buffer
- High-Speed Circuits
- Low Error Voltage

APPLICATIONS

- Direct Logic-Level Interface: TTL/CMOS
- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Solid-State Relays



Device Marking
Top View

VQ1001J
"S" flxxxy

VQ1001P
"S" flxxxy

"S" = Siliconix Logo
f = Factory Code
// = Lot Traceability
xyxy = Date Code

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Single	Total Quad
Drain-Source Voltage		V_{DS}	30	
Gate-Source Voltage	VQ1001J	V_{GS}	± 30	
	VQ1001P		± 20	
Continuous Drain Current ($T_J = 150^\circ\text{C}$)	$T_A = 25^\circ\text{C}$	I_D	0.83	
	$T_A = 100^\circ\text{C}$		0.53	
Pulsed Drain Current ^a		I_{DM}	3	
Power Dissipation (Single)	$T_A = 25^\circ\text{C}$	P_D	1.3	2
	$T_A = 100^\circ\text{C}$		0.52	0.8
Thermal Resistance, Junction-to-Ambient (Single)		R_{thJA}	96	62.5
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	

Notes

a. Pulse width limited by maximum junction temperature.

SPECIFICATIONS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Limits			Unit
			Min	Typ ^a	Max	
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 10 μA	30	45		V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 1 mA	0.8	1.5	2.5	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±16 V			±100	nA
		T _J = 125°C			±500	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30 V, V _{GS} = 0 V			10	μA
		V _{DS} = 24 V, V _{GS} = 0 V, T _J = 125°C			500	
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 10 V, V _{GS} = 12 V	2	3.5		A
Drain-Source On-Resistance ^b	r _{DS(on)}	V _{GS} = 5 V, I _D = 0.2 A		1.2	1.75	Ω
		V _{GS} = 12 V, I _D = 1 A		0.8	1	
		T _J = 125°C		1.5	2	
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 0.5 A	200	500		mS
Dynamic						
Input Capacitance	C _{iss}	V _{DS} = 15 V, V _{GS} = 0 V, f = 1 MHz		38	110	pF
Output Capacitance	C _{oss}			33	110	
Reverse Transfer Capacitance	C _{rss}			8	35	
Switching ^c						
Turn-On Time	t _{ON}	V _{DD} = 15 V, R _L = 23 Ω, I _D ≅ 0.6 A V _{GEN} = 10 V, R _G = 25 Ω		9	30	ns
Turn-Off Time	t _{OFF}			14	30	







Notes

- a. For DESIGN AID ONLY, not subject to production testing.
b. Pulse test: $PW \leq 300\text{ }\mu\text{s}$ duty cycle $\leq 2\%$.
c. Switching time is essentially independent of operating temperature.







VNDQ03



TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)



TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.