HIGH TEMPERATURE

Shielded Power Inductors – XAL1010

- High current – up to 98.8 A
- Very low DCR – 0.33 mOhms
- Soft saturation makes them ideal for VRM/VRD applications.

Core material Composite
Core and winding loss See www.coilcraft.com/coreloss
Environmental RoHS compliant, halogen free
Terminations RoHS compliant tin-silver (96.5/3.5) over copper. Other terminations available at additional cost.
Weight 5.7 – 6.3 g
Ambient temperature –40°C to +125°C with Irms current, +125°C to +165°C with derated current.
Storage temperature Component: –40°C to +130°C. Tape & reel packaging: –40°C to +80°C
Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles
Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)
Failures in Time (FIT) / Mean Time Between Failures (MTBF) 38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332
Packaging 300/13″ reel Plastic tape: 24 mm wide, 0.4 mm thick, 16 mm pocket spacing, 10.21 mm pocket depth
PCB washing Only pure water or alcohol recommended

Part number[1]	Inductance[2] ±20% (µH)	DCR (mOhms)[3] typ	DCR (mOhms)[3] max	SRF typ[4] (MHz)	Isat[5] (A)	Irms (A)[6] 20°C rise	Irms (A)[6] 40°C rise
XAL1010-221ME_	0.22	0.33	0.37	115	98.8	41.0	55.5
XAL1010-451ME_	0.45	0.60	0.66	66	70.5	40.0	53.0
XAL1010-102ME_	1.0	1.00	1.10	42	55.0	32.0	43.5
XAL1010-152ME_	1.5	1.60	1.76	33	36.6	31.0	40.5
XAL1010-222ME_	2.2	2.55	2.80	22	34.0	24.5	32.0
XAL1010-332ME_	3.3	3.70	4.10	21	27.4	18.2	25.0
XAL1010-472ME_	4.7	5.20	5.70	19	25.4	17.5	24.0
XAL1010-562ME_	5.6	6.30	6.93	16	23.6	15.7	21.2
XAL1010-682ME_	6.8	8.10	8.90	14	21.8	14.0	18.5
XAL1010-822ME_	8.2	11.70	12.90	12	18.3	12.9	17.1
XAL1010-103ME_	10	13.40	14.75	11	17.5	11.5	15.5
XAL1010-153ME_	15	16.90	18.60	9	15.5	9.9	13.8

Irms Testing

Irms testing was performed on 0.75 inch wide × 0.25 inch thick copper traces in still air.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

1. When ordering, please specify **termination** and **packaging** coded:

XAL1010-153MED

Termination: **E** = RoHS compliant tin-silver over copper.
Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or **S** = non-RoHS tin-lead (63/37).
Packaging: **D** = 13″ machine-ready reel. EIA-481 embossed plastic tape (300 parts per full reel).
B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added ($25 charge), use code letter D instead.

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc.
3. DCR measured on a micro-ohmmeter.
4. SRF measured using Agilent/HP 4395A or equivalent.
5. DC current at which the inductance drops 30% (typ) from its value without current.
6. Current that causes the specified temperature rise from 25°C ambient.
7. Electrical specifications at 25°C.

Refer to Doc 362 “Soldering Surface Mount Components” before soldering.

Coilcraft®
www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 804-1 Revised 11/15/11

© Coilcraft Inc. 2011
This product may not be used in medical or high risk applications without prior Coilcraft approval.
Specifications subject to change without notice.
Please check our web site for latest information.

HIGH TEMPERATURE

RoHS Halogen Free

Shielded Power Inductors – XAL1010

Typical L vs Current

























Coilcraft®
www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 804-2 Revised 12/12/11

© Coilcraft Inc. 2011
This product may not be used in medical or high risk applications without prior Coilcraft approval.
Specifications subject to change without notice.
Please check our web site for latest information.

HIGH TEMPERATURE

RoHS Halogen Free

Shielded Power Inductors – XAL1010

Typical L vs Frequency



Irms Derating







Dash number	A ±0.008 in ±0,20 mm (in / mm)	B (in / mm)
-221	0.406 / 10.31	0.445 / 11.31
-451	0.406 / 10.31	0.445 / 11.31
-102	0.406 / 10.31	0.445 / 11.31
-152	0.390 / 9.91	0.421 / 10.71
-222	0.374 / 9.51	0.398 / 10.11
-332	0.358 / 9.11	0.374 / 9.51
-472	0.358 / 9.11	0.374 / 9.51
-562	0.358 / 9.11	0.374 / 9.51
-682	0.351 / 8.91	0.362 / 9.21
-822	0.343 / 8.71	0.351 / 8.91
-103	0.343 / 8.71	0.351 / 8.91
-153	0.343 / 8.71	0.351 /8.91





Recommended Land Pattern

Dimensions are in inches / mm

Coilcraft®
www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

© Coilcraft Inc. 2011
This product may not be used in medical or high risk applications without prior Coilcraft approval.
Specifications subject to change without notice.
Please check our web site for latest information.