

Phase Control Thyristors (Hockey PUK Version), 790 A



B-PUK (TO-200AC)

FEATURES

- Center amplifying gate
- Metal case with ceramic insulator
- International standard case B-PUK (TO-200AC)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

TYPICAL APPLICATIONS

- DC motor control
- Controlled DC power supplies
- AC controllers

PRIMARY CHARACTERISTICS	
$I_{T(AV)}$	790 A
V_{DRM}/V_{RRM}	2000 V, 2200 V, 2400 V
V_{TM}	2.07 V
I_{GT}	100 mA
T_J	-40 °C to +125 °C
Package	B-PUK (TO-200AC)
Circuit configuration	Single SCR

MAJOR RATINGS AND CHARACTERISTICS			
PARAMETER	TEST CONDITIONS	VALUES	UNITS
$I_{T(AV)}$		790	A
	T_{hs}	55	°C
$I_{T(RMS)}$		1557	A
	T_{hs}	25	°C
I_{TSM}	50 Hz	10 100	
	60 Hz	10 700	A
I^2t	50 Hz	510	
	60 Hz	475	KA ² s
V_{DRM}/V_{RRM}		2000 to 2400	V
t_q	Typical	200	μs
T_J		-40 to +125	°C

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS				
TYPE NUMBER	VOLTAGE CODE	V_{DRM}/V_{RRM} , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE V	V_{RSM} , MAXIMUM NON-REPETITIVE PEAK VOLTAGE V	I_{DRM}/I_{RRM} MAXIMUM AT $T_J = T_{J \text{ MAXIMUM}}$ mA
VS-ST650C..L	20	2000	2100	80
	22	2200	2300	
	24	2400	2500	

ABSOLUTE MAXIMUM RATINGS							
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES	UNITS	
Maximum average on-state current at heatsink temperature	$I_{T(AV)}$	180° conduction, half sine wave Double side (single side) cooled			790 (324) 55 (85)	A °C	
Maximum RMS on-state current	$I_{T(RMS)}$	DC at 25 °C heatsink temperature double side cooled			1857	A	
Maximum peak, one-cycle non-repetitive surge current	I_{TSM}	$t = 10 \text{ ms}$	No voltage reapplied	Sinusoidal half wave, initial $T_J = T_J$ maximum	10 100		
		$t = 8.3 \text{ ms}$	100 % V_{RRM} reapplied		10 700		
		$t = 10 \text{ ms}$	No voltage reapplied		8600		
		$t = 8.3 \text{ ms}$	100 % V_{RRM} reapplied		9150		
Maximum I^2t for fusing	I^2t	$t = 10 \text{ ms}$	No voltage reapplied	Sinusoidal half wave, initial $T_J = T_J$ maximum	510	kA ² s	
		$t = 8.3 \text{ ms}$	100 % V_{RRM} reapplied		475		
		$t = 10 \text{ ms}$	No voltage reapplied		370		
		$t = 8.3 \text{ ms}$	100 % V_{RRM} reapplied		347		
Maximum $I^2\sqrt{t}$ for fusing	$I^2\sqrt{t}$	$t = 0.1 \text{ to } 10 \text{ ms}$, no voltage reapplied			5100	kA ² \sqrt{s}	
Low level value of threshold voltage	$V_{T(TO)1}$	$(16.7 \% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)})$, $T_J = T_J$ maximum			1.04	V	
High level value of threshold voltage	$V_{T(TO)2}$	$(I > \pi \times I_{T(AV)})$, $T_J = T_J$ maximum			1.13		
Low level value of on-state slope resistance	r_{t1}	$(16.7 \% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)})$, $T_J = T_J$ maximum			0.61	mΩ	
High level value of on-state slope resistance	r_{t2}	$(I > \pi \times I_{T(AV)})$, $T_J = T_J$ maximum			0.35		
Maximum on-state voltage	V_{TM}	$I_{pk} = 1700 \text{ A}$, $T_J = T_J$ maximum, $t_p = 10 \text{ ms}$ sine pulse			2.07	V	
Maximum holding current	I_H	$T_J = 25 \text{ °C}$, anode supply 12 V resistive load			600	mA	
Typical latching current	I_L				1000		

SWITCHING						
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES	UNITS
Maximum non-repetitive rate of rise of turned-on current	di/dt	Gate drive 20 V, 20 Ω, $t_r \leq 1 \mu\text{s}$ $T_J = T_J$ maximum, anode voltage $\leq 80 \% V_{DRM}$			1000	A/μs
Typical delay time	t_d	Gate current 1 A, $di/dt = 1 \text{ A}/\mu\text{s}$ $V_d = 0.67 \% V_{DRM}$, $T_J = 25 \text{ °C}$			1.0	μs
Maximum turn-off time	t_q	$I_{TM} = 750 \text{ A}$, $T_J = T_J$ maximum, $di/dt = 60 \text{ A}/\mu\text{s}$ $V_R = 50$, $dV/dt = 20 \text{ V}/\mu\text{s}$, Gate 0 V 100 Ω, $t_p = 500 \mu\text{s}$			200	

BLOCKING						
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES	UNITS
Maximum critical rate of rise of off-state voltage	dV/dt	$T_J = T_J$ maximum linear to 80 % rated V_{DRM}			500	V/μs
Maximum peak reverse and off-state leakage current	I_{RRM} , I_{DRM}	$T_J = T_J$ maximum, rated V_{DRM}/V_{RRM} applied			80	mA

TRIGGERING		SYMBOL	TEST CONDITIONS	VALUES		UNITS
PARAMETER				TYP.	MAX.	
Maximum peak gate power	P_{GM}		$T_J = T_J$ maximum, $t_p \leq 5$ ms	10.0		
Maximum average gate power	$P_{G(AV)}$		$T_J = T_J$ maximum, $f = 50$ Hz, $d\% = 50$	2.0		W
Maximum peak positive gate current	I_{GM}			3.0		A
Maximum peak positive gate voltage	$+ V_{GM}$		$T_J = T_J$ maximum, $t_p \leq 5$ ms	20		
Maximum peak negative gate voltage	$- V_{GM}$			5.0		V
DC gate current required to trigger	I_{GT}	$T_J = -40$ °C $T_J = 25$ °C $T_J = 125$ °C	Maximum required gate trigger current/voltage are the lowest value which will trigger all units 12 V anode to cathode applied	200	-	mA
DC gate voltage required to trigger	V_{GT}	$T_J = -40$ °C $T_J = 25$ °C $T_J = 125$ °C		100	200	
DC gate current not to trigger	I_{GD}			50	-	
DC gate voltage not to trigger	V_{GD}	$T_J = T_J$ maximum		2.5	-	V
				1.8	3.0	
				1.1	-	
Maximum gate current/voltage not to trigger is the maximum value which will not trigger any unit with rated V_{DRM} anode to cathode applied				10		mA
					0.25	V

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES	UNITS
Maximum operating temperature range	T_J				-40 to 125	°C
Maximum storage temperature range	T_{Stg}				-40 to 150	
Maximum thermal resistance, junction to heatsink	R_{thJ-hs}	DC operation single side cooled		0.073		K/W
DC operation double side cooled				0.031		
Maximum thermal resistance, case to heatsink	R_{thC-hs}	DC operation single side cooled		0.011		
DC operation double side cooled				0.006		
Mounting force, ± 10 %				14 700 (1500)	N (kg)	
Approximate weight				255	g	
Case style		See dimensions - link at the end of datasheet		B-PUK (TO-200AC)		

ΔR_{thJ-hs} CONDUCTION						
CONDUCTION ANGLE	SINUSOIDAL CONDUCTION		RECTANGULAR CONDUCTION		TEST CONDITIONS	UNITS
	SINGLE SIDE	DOUBLE SIDE	SINGLE SIDE	DOUBLE SIDE		
180°	0.009	0.009	0.006	0.006	$T_J = T_J$ maximum	K/W
120°	0.011	0.011	0.011	0.011		
90°	0.014	0.014	0.015	0.015		
60°	0.020	0.020	0.021	0.021		
30°	0.036	0.036	0.036	0.036		

Note

- The table above shows the increment of thermal resistance R_{thJ-hs} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - On-State Power Loss Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 6 - On-State Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current
Single and Double Side Cooled




Fig. 8 - Maximum Non-Repetitive Surge Current
Single and Double Side Cooled




Fig. 9 - On-State Voltage Drop Characteristics




Fig. 10 - Thermal Impedance Z_{thJ-hs} Characteristics




Fig. 11 - Gate Characteristics

ORDERING INFORMATION TABLE

Device code	VS-	ST	65	0	C	24	L	1	-
	1	2	3	4	5	6	7	8	9


- 1** - Vishay Semiconductors product
- 2** - Thyristor
- 3** - Essential part number
- 4** - 0 = converter grade
- 5** - C = ceramic PUK
- 6** - Voltage code x 100 = V_{RRM} (see Voltage Ratings table)
- 7** - L = PUK case B-PUK (TO-200AC)
- 8** - 0 = eyelet terminals (gate and auxiliary cathode unsoldered leads)
1 = fast-on terminals (gate and auxiliary cathode unsoldered leads)
2 = eyelet terminals (gate and auxiliary cathode soldered leads)
3 = fast-on terminals (gate and auxiliary cathode soldered leads)
- 9** - Critical dV/dt : • none = 500 V/ μ s (standard selection)
• L = 1000 V/ μ s (special selection)

LINKS TO RELATED DOCUMENTS	
Dimensions	www.vishay.com/doc?95076

B-PUK (TO-200AC)

DIMENSIONS in millimeters (inches)

Creepage distance: 36.33 (1.430) minimum
 Strike distance: 17.43 (0.686) minimum



Quote between upper and lower pole pieces has to be considered after application of mounting force (see thermal and mechanical specification)

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.